



Top—View approaching station from the east Bottom—One of the three-track cantilever bridges

New York Central's Reconstruction Program at South Bend Involves

New Electric Interlocking

with Design Which Minimizes Maintenance Costs

By G. E. Beck

Assistant to Signal Engineer, New York Central, Lines West, Cleveland, Ohio

THE New York Central's recent reconstruction program at South Bend, Ind., motivated by the desirability of separating the grade at important heavy-traffic street crossings, involved the construction of an extensive electric interlocking plant. The track layout within this territory includes: The ends of double track, at each end of the plant, leading to the center, or yard, tracks; two double-track junctions of the Grand Trunk; a double-track junction with its own Illinois division line; and a single-track crossing of the latter over its four-track main line. The distance between the east and west home signals is approximately 3.68 miles.

Where, formerly, 18 city street crossings presented a serious crossing-protection problem, there is now an elevated earthwork track structure nearly three miles long with 14 street bridges. A new passenger station was built, which also accommodates the Grand Trunk as a tenant line. The traffic through this plant each 24 hours consists of 40 Grand Trunk trains, 70 New York Central trains, and about 6 yard movements.

The interlocking installation is based on the principles of the General Railway Signal Company's all-

electric system, the Model-5B interlocking machine, with latch locking, being used. This machine has 259 working levers, 9 spare levers, and 36 lever spaces in a 304-lever frame, which is enclosed in a steel cabinet, finished in olive green. Electric locking is effected by the use of 102 forced-drop electric locks, which are applied to the lever latches. Ninety-two time releases, adjustable from 0 to 90 sec. operation time are applied to various levers, as required. In addition, the machine is equipped with 662 six-way banks of low-voltage relay-type controller contacts, 2 ammeters, 1 voltmeter, and G. R. S. standard ground-detector switches. It is proposed to install, at a later date, transit lights over the switch levers to indicate that the switch is full normal or full reverse. Switchboard lamps will be used, and will be mounted in a hole drilled in the case of the machine. The indication will be effected by inserting a 100-ohm relay in series with the SS relay, the transit light to be controlled through a back contact of this series relay.

An illuminated track diagram, 3 ft. wide by 24 ft. long, mounted on the wall back of the machine, consists of 111 track sections, outlined in color, each

